


TUNG-SOL

PENTODE

MINIATURE TYPE



GLASS BULB


COATED UNIPOTENTIAL CATHODE

HEATER

4.2 VOLTS 0.45±6% AMP.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

MINIATURE BUTTON
7 PIN BASE

7CM

THE 4BZ6 IS A HIGH TRANSCONDUCTANCE, SEMI-REMOTE CUT-OFF, PENTODE AMPLIFIER. IT IS DESIGNED FOR SERVICE AS AN AUTOMATIC GAIN CONTROLLED IF AMPLIFIER IN 450 MA. SERIES HEATER OPERATED TELEVISION RECEIVERS. THERMAL CHARACTERISTICS OF THE HEATER ARE CONTROLLED SUCH THAT HEATER VOLTAGE SURGES DURING THE WARM-UP CYCLE ARE MINIMIZED PROVIDED IT IS USED WITH OTHER TYPES WHICH ARE SIMILARLY CONTROLLED. WITH THE EXCEPTION OF HEATER RATINGS, ITS CHARACTERISTICS ARE IDENTICAL TO THE 6BZ6.

DIRECT INTERELECTRODE CAPACITANCES

	WITH SHIELD ^A	WITHOUT SHIELD	
GRID TO PLATE: G_1 TO P (MAX.)	.015	.025	μmf
INPUT: G_1 TO (H+K+ G_2 + G_3 +I+S)	7.0	7.0	μmf
OUTPUT: P TO (H+K+ G_2 + G_3 +I+S)	3.0	2.0	μmf

^A EXTERNAL SHIELD #316 CONNECTED TO CATHODE AT SOCKET.

RATINGS^B

INTERPRETED ACCORDING TO DESIGN CENTER VALUES

HEATER VOLTAGE	4.2	VOLTS
MAXIMUM HEATER CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
TOTAL DC AND PEAK	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE		
DC	100	VOLTS
TOTAL DC AND PEAK	200	VOLTS
MAXIMUM PLATE VOLTAGE	350	VOLTS
MAXIMUM GRID #2 VOLTAGE	SEE RATING CURVE	
MAXIMUM PLATE DISSIPATION	2.3	WATTS
MAXIMUM GRID #2 DISSIPATION	0.55	WATT
MAXIMUM GRID #2 SUPPLY VOLTAGE	350	VOLTS
MAXIMUM POSITIVE DC GRID #1 VOLTAGE	0	VOLTS
HEATER WARM-UP TIME (APPROX.)*	11.0	SECONDS

* HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 3 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL



CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A₁ AMPLIFIER


HEATER VOLTAGE	4.2	VOLTS
HEATER CURRENT	0.45±6%	AMP.
PLATE VOLTAGE	125	VOLTS
GRID #2 VOLTAGE	125	VOLTS
GRID #3 VOLTAGE		
CATHODE BIAS RESISTOR	56	OHMS
PLATE RESISTANCE (APPROX.)	0.26	MEGOHM
TRANSCONDUCTANCE	8 000	μMHOS
PLATE CURRENT	14	MA.
GRID #2 CURRENT	3.6	MA.
GRID #1 VOLTAGE (APPROX.) FOR $G_m = 50$ μMHOS	-19	VOLTS
TRANSCONDUCTANCE ($E_{c1} = -4.5$ V., $R_k = 0$)	700	μMHOS


^B DESIGN MAXIMUM RATINGS ARE THE LIMITING VALUES EXPRESSED WITH RESPECT TO BOGIE TUBES AT WHICH SATISFACTORY TUBE LIFE CAN BE EXPECTED TO OCCUR IN THE TYPES OF SERVICE FOR WHICH THE TUBE IS RATED. THEREFORE, THE EQUIPMENT DESIGNER MUST ESTABLISH THE CIRCUIT DESIGN SO THAT INITIALLY AND THROUGHOUT EQUIPMENT LIFE NO DESIGN MAXIMUM VALUE IS EXCEEDED WITH A BOGIE TUBE UNDER THE WORST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, AND ENVIRONMENTAL CONDITIONS.



PRINTED IN U. S. A.

4BZ6





PRINTED IN U. S. A.