


DOUBLE DIODE-TRIODE
DOFFELDIODE-TRIODE

Heating : indirect; parallel supply $V_f = 4,0V$
 Chauffage: indirect; alimentation- parallèle $I_f = 0,65A$
 Heizung : indirekt; Parallelspeisung

Dimensions in mm
 Dimensions en mm
 Abmessungen in mm



Base, culot, Sockel: P

Capacitances
 Capacités
 Kapazitäten

| | | |
|------------|---|----------|
| C_{d1} | = | 2,3 pF |
| C_{d2} | = | 3,0 pF |
| C_{d1d2} | < | 0,5 pF |
| C_{d1g} | < | 0,003 pF |
| C_{d2g} | < | 0,003 pF |

Typical characteristics
 Caractéristiques types
 Kenndaten

| | | |
|-------|---|-----------------|
| V_a | = | 250 V |
| V_g | = | -7 V |
| I_a | = | 4 mA |
| S | = | 2 mA/V |
| R_i | = | 13,5 k Ω |
| μ | = | 27 |

Limiting values
 Caractéristiques limites
 Grenzdaten

| | | | | | |
|----------------------|--------|--------|-------------|--------|----------------|
| V_{a0} | = max. | 550 V | I_k | = max. | 10 mA |
| V_a | = max. | 250 V | R_g | = max. | 1,5 M Ω |
| W_a | = max. | 1,5 W | V_{kf} | = max. | 50 V |
| $V_g(I_g=+0,3\mu A)$ | = max. | -1,3 V | R_{kf} | = max. | 20 k Ω |
| Each diode | | | V_{dinvp} | = max. | 420 V |
| Chaque diode | | | I_d | = max. | 0,8 mA |
| Jede Diode | | | I_{dp} | = max. | 50 mA |

PHILIPS



*Electronic
Tube*

HANDBOOK

| page | ABC1 sheet | date |
|-------------|-----------------------|-------------|
| 1 | 1 | 1953.12.12 |
| 2 | FP | 1999.06.26 |