




## TRIODE

Heating : indirect; parallel supply  $V_f = 4,0 \text{ V}$   
 Chauffage: indirect; alimentation- parallèle  $I_f = 0,65 \text{ A}$   
 Heizung : indirekt; Parallelspeisung

Dimensions in mm  
 Dimensions en mm  
 Abmessungen in mm



Base, culot, Sockel: P

Capacitances  
 Capacités  
 Kapazitäten

$C_a = 4,5 \text{ pF}$   
 $C_g = 4,9 \text{ pF}$   
 $C_{ag} = 1,7 \text{ pF}$

Typical characteristics  
 Caractéristiques types  
 Kenndaten

$V_A = 250 \text{ V}$   
 $V_g = -5,5 \text{ V}$   
 $I_a = 6 \text{ mA}$   
 $S = 2,5 \text{ mA}$   
 $R_i = 12 \text{ k}\Omega$   
 $\mu = 30$

Limiting values  
 Caractéristiques limites  
 Grenzdaten

$V_{a0} = \text{max. } 550 \text{ V}$   
 $V_a = \text{max. } 250 \text{ V}$   
 $W_a = \text{max. } 2 \text{ W}$   
 $V_g(I_g = +0,3 \mu\text{A}) = \text{max. } -1,3 \text{ V}$   
 $I_k = \text{max. } 10 \text{ mA}$   
 $R_g = \text{max. } 1,5 \text{ M}\Omega$   
 $V_{kf} = \text{max. } 50 \text{ V}$   
 $R_{kf} = \text{max. } 20 \text{ k}\Omega$

**PHILIPS**



*Electronic  
Tube*

**HANDBOOK**

<b>page</b>	<b>AC2 sheet</b>	<b>date</b>
1	2	1953.12.12
2	FP	1999.06.26