

**Betriebsdaten:**  
 Typical operation:  
 Exemple d'utilisation:

$U_f$  . . . 2,5 V  
 $I_f$  . . . . . 5 A  
 $U_a$  . max 4500 V  
 $I_a$  . max 500 mA



**Prüfdaten:**  
 Test operation:  
 Vérification:

$U_f$  . . . . . 2,5 V ~  
 $U_a$  . . . . . 60 V ~

Röhrenmeßgerät Modell W 19

MAX FUNKE, Adenau-Eifel 6. 59.

**3 B 28**  
**DCX 4/1000**

2 V/400 A DX 2  
 2 V/400 B GXU 1  
 3825 A RR 3-250  
 3828 TH 5221V/B  
 AX 224 VX 550 A  
 CV 1835


**DCG 4/1000 G**  
**3 B 25**

248 A 866 AX AG 866 A  
 249 B 866 B AH 201  
 249 C 866 E C 866  
 816 966 C 866 A  
 866 3572 CE 866 A  
 866 A 38166 CV 32

CV 724  
 CV 1261  
 DQ 2

EE 866 PA 5021 UE 966  
 ESU 866 RG 3/250 A UE 966 A  
 F 366 A RG 250/3000 UX 866  
 GL 866 A RK 866 VH 550 A  
 GU 12 T 866 A VT 46 A  
 NU 866 A TH 5021 B WL 866 A

Gleichrichter, gasgefüllt / Gas rectifier / Rectifier à gaz.



Unbrauchbar  
 mauvais / Bad

?

**G u t**  
 Good / Bon

